

# 50 Hz RANGE

## Central Area Model Range

**Power  
Generation**

Our energy working for you.™

ISSUE 14 – OCTOBER 08

Model Name	Previous Model Name	Standby Ratings		Prime Ratings		Engine Model	Standard Alternator	Standard controller	EU/TAL	Sound Enclosure
		kVA	kW	kVA	kW					
C11 D5		11	8.8	10	8	D1703	BCI164B	1301	N/A	●
C15 D5		15	12	13	10.4	D1703	BCI164D	1301	N/A	●
C22 D5		22	17.6	20	16	4B3.3G1	BCI184E	1301		●
C33 D5**		33	26.4	30	24	4B3.3G1	BCI184G	1301		●
C33 D5*		33	26.4	30	24	4BT3.3G3	UCI224C	1.1	II	●
C38 D5**		38	30.4	35	28	4B3.3G1	BCI184H	1301		●
C38 D5*		38	30.4	35	28	4BT3.3G3	UCI224C	1.1	II	●
C44 D5*		44	35.2	40	31.68	4BT3.3G3	UCI224C	1.1	II	●
C55 D5**		55	44	50	40	4BT3.3G2	UCI224D	1301		●
C55 D5*		55	44	50	40	4BT3.3G3	UCI224D	1.1	II	●
C70 D5		70	56	63	50	4BT3.9G4	UCI224F	1301	4g	●
C80 D5		80	64	72	58	4BTA3.9G1	UCI224F	1301		●
C110 D5		110	88	100	80	4ISBeG1	UCI274C	1301	4g	●
C150 D5		150	120	136	109	6BTA5.9G2	UCI274E	1301		●
C150 D5e		150	120	136	109	QSB7G3	UCI274E	1.1	IIIA	●
C175 D5e*		175	140	158	126	QSB7G3/G5	UCI274F	1.1/1.2	IIIA	●
C200 D5e*		200	160	182	146	QSB7G5	UC274H	1.2	IIIA	●
C220 D5e*		220	176	200	160	QSB7G5	UC274H	1.2	IIIA	●
C200 D5**		200	160	182	146	6CTAA8.3G1	UC274H	1301	4g	●
C220 D5**		220	176	200	160	6CTAA8.3G1	UC274H	1301	4g	●
C250 D5		250	200	227	182	6CTAA8.3G2	UCD274J	1301	4g	●
C275 D5		275	220	250	200	QSL9G5	UCD274K	1301	4g	●
C300 D5		300	240	275	220	QSL9G5	HC14D	1301	4g	●
C330 D5		330	264	300	240	QSL9G5	HC14D	1301	4g	●
C350 D5		350	280	320	256	NTR855G6	HC14E	2100		●
C400 D5		400	320	360	288	NTA855G4	HC14F	2100		●
C440 D5		440	352	400	320	NTA855G7	HC5C	2100		●
C500 D5		500	400	450	360	QXS15G8	HC5C	2100	II	●
C550 D5		550	440	500	400	QXS15G8	HC5D	2100	II	●
C700 D5	DFGB	706	565	640	512	VTA28G5	HC5F	3100		ISO20
C825 D5A	DFGD	825	660	750	600	VTA28G6	HC6G	3100		ISO20
C825 D5		825	660	750	600	QSK23G3	HC6G	2100		x
C900 D5		900	720	820	656	QSK23G3	HC6H	2100		x
C1000 D5	DFHC	1041	833	939	751	QST30G3	HC6J	3100		ISO20
C1100 D5	DFHD	1110	888	1000	800	QST30G4	HC6K	3100		x
C1100 D5B	DFJD	1132	906	1029	823	KTA38G5	HC6K	3100		HC40
C1400 D5		1400	1120	1250	1000	KTA50G3	P7B	2100		HC40
C1675 D5		1675	1340	1400	1120	KTA50G8	P7D	2100		HC40
C1675 D5A		1675	1340	1500	1200	KTA50G8S	P7D	2100		HC40
C2000 D5		2063	1650	1875	1500	QSK60G3	P7F	3201		x
C2250 D5		2250	1800	2000	1600	QSK60G4	P7G	3201		x
C2500 D5A		2500	2000	2250	1800	QSK60G8	P80R	3201	4g	x
C3300 D5	DQLB	3325	2660	3000	2400	QSK78G6	LVS1824G	3200		x

\* Forthcoming product

\*\* Product to be obsolete

# 60 Hz RANGE

## Central Area Model Range

**Power  
Generation**

Our energy working for you.™

ISSUE 14 – OCTOBER 08

Model Name	Previous Model Name	Standby Ratings		Prime Ratings		Engine Model	Standard Alternator	Standard controller	Sound Enclosure
		kVA	kW	kVA	kW				
C11 D6		13.8	11	12.5	10	D1703	BCI164B	1301	●
C15 D6		18.8	15	16.3	13	D1703	BCI164D	1301	●
C25 D6		30	24	27.5	22	4B3.3G1	BCI184E	1301	●
C30 D6**		37.5	30	33.8	27	4B3.3G1	BCI184G	1301	●
C30 D6*		37.5	30	33.8	27	4BT3.3G3	UCI224C	1.1	●
C35 D6**		43.8	35	40	32	4B3.3G1	BCI184H	1301	●
C35 D6*		43.8	35	40	32	4BT3.3G3	UCI224C	1.1	●
C40 D6*		50	40	45	36	4BT3.3G3	UCI224C	1.1	●
C50 D6**		62.5	50	56.3	45	4BT3.3G2	UCI224D	1301	●
C50 D6*		62.5	50	56.3	45	4BT3.3G3	UCI224D	1.1	●
C60 D6		75	60	69	55	4BT3.9G4	UC224F	1301	●
C70 D6		88	70	81	65	4BTA3.9G2	UC224F	1301	●
C100 D6		125	100	113	90	4ISBeG1	UC274C	1301	●
C125 D6e		156	125	141	113	QSB7G3	UC274E	1.1	●
C135 D6		169	135	153	122	6BTA5.9G2	UC224F	1301	●
C150 D6e*		188	150	169	135	QSB7G3/G5	UC274F	1.1/1.2	●
C175 D6e*		219	175	200	160	QSB7G5	UC274H	1.2	●
C200 D6e*		250	200	225	180	QSB7G5	UC274H	1.2	●
C180 D6**		225	180	206	165	6CTAA8.3G1	UC274H	1301	●
C200 D6**		250	200	225	180	6CTAA8.3G1	UC274H	1301	●
C225 D6		281	225	256	205	6CTAA8.3G2	UCD274J	1301	●
C250 D6		313	250	281	225	QSL9G5	UCD274K	1301	●
C275 D6		344	275	313	250	QSL9G5	HC14D	1301	●
C300 D6		375	300	344	275	QSL9G5	HC14D	1301	●
C350 D6		438	350	400	320	NTA855G3	HC4F	2100	●
C400 D6		500	400	456	365	NTA855G5	HC5C	2100	●
C450 D6		563	450	513	410	QSX15G9	HC5C	2100	●
C500 D6		625	500	563	450	QSX15G9	HC5D	2100	●
C600 D6	DFGB	754	603	681	545	VTA28G5	HC5F	3100	ISO20
C750 D6		938	750	850	680	QSK23G3	HC6G	2100	x
C800 D6		1000	800	906	725	QSK23G3	HC6G	2100	x
C900 D6	DFHC	1156	925	1044	835	QST30G3	HC6J	3100	ISO20
C1000 D6	DFHD	1265	1012	1150	920	QST30G4	HC6K	3100	x
C1000 D6B	DFJD	1276	1020	1160	928	KTA38G4	HC6K	3100	HC40
C1250 D6		1588	1270	1400	1120	KTA50G3	P7B	2100	HC40
C1500 D6		1931	1545	1608	1286	KTA50G9	P7C	2100	HC40
C2000 D6		2500	2000	2281	1825	QSK60G6	P7F	3201	x
C2250 D6A		2813	2250	NA	NA	QSK60G9	P7G	3201	x
2500 DQLC		3125	2500	2920	2336	QSK78G6	LVS1804R	3201	x

\* Forthcoming product

\*\* Product to be obsolete

For Rating Definitions refer to Data Sheet.

Cummins Power Generation Limited  
Manston Park, Columbus Avenue  
Manston, Ramsgate  
Kent CT12 5BF, UK  
Telephone: +44 (0)1843 255000  
Fax: +44 (0)1843 255002  
Email: cpg.uk@cummins.com  
www.cumminspower.com  
www.cummins.com

See your distributor for more information.

Cummins is a registered trademark of Cummins Inc.